



Charles van Gelder Importers, Inc.
 1680 US Hwy 41 South | Calhoun, GA 30701
 p. 706 602 4186 | f. 706 602 4191

| PRODUCT SPECIFICATIONS DOMINATOR TILE | | |
|--|--|---|
| PRODUCT COMPOSITION | STANDARD / NORMS | DATA |
| Manufacturing Process | DIN 61151 | Needle felt |
| Surface Aspect | ISO 2424 | Diagonal pattern |
| Fiber | CEE 83/623 | 100% Solution dyed polypropylene |
| Primary Backing | ISO 2424 | Bitumen or TacFast TM |
| PRODUCT DIMENSION | | |
| Pile Height (+ or - 0.5 mm) | ISO 1765 | .375 inch |
| Total Height (+ or - 7.5%) | ISO 1765 | .50 inch |
| Pile Weight (+ or - 7.5%) | ISO 8543 | 57 oz/sy |
| Total Weight (+ or - 7.5%) | ISO 8543 | 169 oz/sy |
| Tile Size (+ or - 2%) | ISO 3018 | 19.69 x 19.69 |
| Packaging | | 12 tiles per box or 32.5 sq.ft. |
| ELECTROSTATIC PROPERTIES | | |
| Stability | EN 986 | Pass |
| Walk on Test | ISO TR 6356 | < 2kV |
| Electrical Resistivity | IBM / ICL | Pass, for R.H. > or = 40% |
| Sound Insulation | ISO 140-8 | > or = 24dB |
| Electorstatic Propensity | EN 1815 | Permanently Anti-Static |
| Thermal Retention | ISO 11092 | 0.13 m K/W Pass |
| COLOR FASTNESS | | |
| To Light | ISO 105 B02 | 5 |
| To Water | ISO 105 E01 | 5 |
| To Shampoo | BS 1006 | 5 |
| To Rubbing dry & wet | ISO 105X12 | 4 - 5 dry/wet |
| FLAMMABILITY RATING | | |
| Radiant Panel Test | ASTM E648 / DIN 4102 | Passes Federal Flamm. Standard |
| Pill Test | ISO 6925 / ASTM D2859 | Pass |
| Hot Metal Nut Test | BS 4790/BS 5287 | Pass |
| LEED | | |
| MR Credit 4 | LEED-NC v. 3 For 1 - 2 points: \$ value of all | 50% recycled post consumer |
| IEQ Credit 4.1 | LEED-NC v. 3 For 1 point: low-emitting adhesive with a VOC of 50 g/l or less for indoor releasable carpet adhesive | Releasable VOC 0 g/l |
| IEQ Credit 5 | LEED-NC v. 3 For 1 point: semi-permanently installed entrance system at leastt 10' in length and maintained on a weekly basis. | This carpet tile is a semi permanent installation |